

KS-HDIP007

Day/Night 15pcs Super Flux IR LED



Key features

- Day/Night 15pcs Super Flux IR LED
- IK5 and IP66 Weatherproof. Internal MicroSD
- ICR Day / Night with 2.8-12mm DC Iris Lens

Free Software for Mobile (Android / iPhone / iPad)

Remote setup of camera, fully live display of camera.

Works over LAN / WAN (Internet) connection.



Software

100% fully functional IP camera with multi browser support, Onvif Profile S supports motion detection & edge recording. Embedded Flash video technology inside camera. Supporting PoE or 12v power for all installation types. Supplied with NVR Software supporting up to 64 Channels* Safari, Chrome, IE, Firefox, Opera, all browser compatible!



*Cameras recording in real-time depends on PC Specifications.

Specifications

Parameter	Details
CAMERA	
Sensor	Sony Exmor™ 1/2.8"
Max Resolution / FPS	1920x1080 / 30fps
Min. illumination	0.1Lux @ F1.2 (Color) (0 Lux IR LED On)
Day / Night	True Day / Night with ICR Filter.
IR LEDs	15pc Super Flux IR LED 850nm for 20-25 Meters (65 - 82 feet)
Lens	3.3-12mm Vari-focal IR Corrected / (Optional Fixed Lens 4mm 6mm 8mm 12mm)
Video Output	Service BNC output dangle cable with IP OSD from screw fit panel
Electronic Shutter	Auto / User 1/5 - 1/50, 0000; 50/60Hz software selectable.
PARAMETERS	
Compression	H-264 High Profile (Support Baseline Profile) / MJPEG
Bit Rate (CBR/VBR)	Stream1 50Kbps - 12Mbps ; Stream2 10Kbps - 6Mbps ; Stream3 (Fixed)
Quality Setting	1 - 9 (9 Highest)
Multi- Streaming	User setting of Stream 1/2 at supported Resolutions, Stream3 MJPEG Stream
Brightness / Sharpness	Variable 0~100 / 0~100
Gain Control	Auto / Fixed 8~102db
Orientation	Horizontal Mirror / Vertical Flip
Text Overlay	Time / Date / Camera / Custom OSD
Masking	5 User defined masking areas < 8% of total picture
NETWORK	
Ethernet	1 Ethernet (10/100 Base-T) RJ-45 Connector
TCP/IP	IPv4 / IPv6 (DHCP / Fixed)
Compliance	Onvif v2.2 Profile-S Listed
RTSP Video	Standard RFC2326, Support QuickTime / VLC Player. User security authentication (Enabled / Disabled)
Web Language	English, Chinese, Russian, Polish, (European Languages coming 2013)
Recording Simultaneous.	Local Micro SD Memory, Remote FTP server, TCP/UDP CMS, RTSP connection (stream 1,2 or 3)
Network Protocols:	HTTP, TCP/IP, UDP/IP, RTSP, FTP, DHCP, NTP, PPoE, NTP. Unicast and Multicast supported.
Memory Card Slot	Internal memory card supports Max 64GB. Supports Edge Recording
AUDIO	
Input / Output	1 x RCA Input / 1 x RCA Output @ 1v Line Level
Audio Compression	G711 A-Law, G711 U-Law, RAW_PCM
GENERAL	
Power	12v DC @ 560mA (IR LED On) / PoE Class 3
Temperature	Operating: 14°F to 131°F (-10°C to 55°C) Storage: -4°F to 140°F (-20°C to 60°C)
Operating Humidity	10% - 85% RH
Approvals	CE / FCC / RoHS Compliant / IP66 / IK5
Product Dimensions	265.5 x 69 mm (102/5" x 2 3/4")
Product Weight	0.680KG / 1.496lb