



- Dag/nacht Mini VP Dome met IR LED
- Vandal bestendig IK10 & IP66
- Vaste 3.6mm Lens
- Gratis apps voor Android / iPhone / iPad)
- PoE ondersteuning 12V

Mobiele Software :

IP Cam Watch voor iPhone&iPad te vinden in de Appstore

Easyview voor Android te downloaden via onze website.

Overige Software

100% volledig functioneel met brede ondersteuning voor internet browsers Safari, Chrome, IE, Firefox, Opera.

los app IP Cam Watch iPhone en iPad. Android app Easyview. NVMS Windows, Mac software in ontwikkeling. Wordt geleverd met NVR Software welke tot 64 camera's ondersteund.



Specifications

Parameter	Details
CAMERA	
Sensor	Aptina 1/3" CMOS
Max Resolution / FPS	1280x720 / 30fps with eWDR@ 70dB
Min. illumination	0.2Lux @ F1.2 (Color) (0 Lux IR LED On)
Day / Night	True Day / Night with ICR Filter.
IR LEDs	1pc Super Flux IR LED 850nm for 6 Meters (20 feet)
Lens	3.6mm Fixed Mega Pixel IR Coated. Angle 89°±4°(D)x70°(H)x51.9°(V)
Video Output	Service BNC Video with IP OSD using supplied dangle cable
Electronic Shutter	Auto / User 1/5 - 1/50, 0000; 50/60Hz software selectable.
PARAMETERS	
Compression	H-264 High Profile (Support Baseline Profile) / MJPEG
Bit Rate (CBR/VBR)	Stream1 200Kbps - 8Mbps ; Stream2 100Kbps - 6Mbps ; Stream3 (Fixed)
Quality Setting	1 - 9 (9 Highest)
Multi- Streaming	User setting of Stream 1/2 at supported Resolutions, Stream3 MJPEG Stream
Brightness / Sharpness	Variable 0~100 / 0~100
Gain Control	Auto / Fixed 8~102db
Orientation	Horizontal Mirror / Vertical Flip
Text Overlay	Time / Date / Camera / Custom OSD
Masking	5 User defined masking areas < 8% of total picture
NETWORK	
Ethernet	1 Ethernet (10/100 Base-T) RJ-45 Connector
TCP/IP	IPv4 / IPv6 (DHCP / Fixed)
Compliance	Onvif v2.2 Profile-S Listed
RTSP Video	Standard RFC2326, Support QuickTime / VLC Player. User security authentication (Enabled / Disabled)
Web Language	English, Chinese, Russian, Polish
Recording Simultaneous.	Local Micro SD Memory, Remote FTP server, TCP/UDP CMS, RTSP connection (stream 1,2 or 3)
Network Protocols:	HTTP, TCP/IP, UDP/IP, RTSP, FTP, DHCP, NTP, PPoE, NTP. Unicast and Multicast supported.
Memory Card Slot	Internal memory card supports Max 64GB. Supports Edge Recording
AUDIO	
Input / Output	Optional Microphone: 1 x RCA Input / 1 x RCA Output @ 1v Line Level
Audio Compression	G711 A-Law, G711 U-Law, RAW_PCM
GENERAL	
Power	12V DC @ 335mA (IR LED On) / PoE Class 3 on Ethernet
Temperature	Operating: 14°F to 131°F (-10°C to 55°C) Storage: -4°F to 140°F (-20°C to 60°C)
Operating Humidity	10% - 85% RH
Approvals	CE / FCC / RoHS Compliant / IP66 / IK10
Product Dimensions	100 x 53 mm (4" x 2")
Product Weight	0.3kg / 0.66lb