

KS-IPNVR001



1TB Harde schijf standaard ingebouwd

MODEL		HD NVR
Operating System		Embedded Linux (H.264)
IP Camera	Channel	16 Ch
	Protocol	STL, RTSP & ONVIF
Recording Speed	CIF	480 (30FPS/CH)
	D1	480 (30FPS/CH)
	720P	120 (7.5FPS/CH)
	1080P	80 (5FPS/CH)
Recording Mode	Resolution	CIF, D1, 720p, 1080p
	Mode	Manual, Continuous, Alarm, Motion Record
System Operation		Remote Operation only (Local Display & Playback : Not Available)
Network Function	Protocol	IPV4, ARP, TCP, UDP, ICMP, DHCP, NTP, DNS, DDNS, SMTP, FTP, HTTP, UPnP, RTP, RTCP, RTSP, PPPoE, 3GPP, ONVIF
	PTZ Control	ONVIF Compatibility (PanTilt / Zoom / Preset)
	Transmission	Unicast Transmission
Remote Management	Remote Software	CMS (CentralManager S/W) & MMS (Mobile Viewer) & Mac-Viewer (S/W for Mac OS)
	Web Browser	M/S Internet Explorer, Apple Safari, Google Chrome, Mozilla Firefox, Opera
	Remote P/C O/S	M/S Windows, Apple Mac, Linux
	Operation	Live Monitoring, Playback & System Configuration
Backup Device		Local Backup by USB ODD and Network Backup by CMS
Hard Disk	HDD Bay	2 (Internal Bay)
	Supported HDD	3.5" SATA II/III (Up to 3TB each)
Front Panel	LED Display	4 x LEDs (Power, Status, Record, LAN)
	USB Port	1 x USB : For Backup
Rear Plate	Power Switch	Power On/Off
	Power Connector	12V x 5A D/C
	LAN Port	Gigabit Ethernet (RJ45) : Fixed IP, DHCP & DDNS
	Digital I/O	1 x Digital Output (Relay), 4 x Digital Input (Sensor)
	e-SATA Port	Local Storage Extension through e-SATA Port
	Reset Button	System Reset
System Recovery after Power Failure		Auto-Reboot and Journaling File System
Operating Temperature and Humidity		5~40 °C / 20~80% RH
Dimension (WxDxH)		270 x 215 x 71 mm
Certification		CE & FCC & MIC & WEEE, RoHS